

OXYDECOR VERDERAME

Verderame effect metallic paint

DESCRIPTION

Oxydeco Verderame Isoplam® is a particular decorative paint, which recreates the preciousness of copper and its natural oxidation process, both as a visual aspect and to the touch. It faithfully replicates the change that occurs to metal exposed for a long time to the corrosion of atmospheric agents. It can be used both inside and outside. Verderame does not drip or stain. It can be made in three different variants: Verderame, Verderame Brunito or Verderame Antico.

PREPARATION OF THE SUBSTRATE

Protect all the adjacent surfaces and objects that should not be treated with Oxydeco Isoplam® with Isocolor® Polyethylene Replacement.
Oxydeco Verderame can be applied on concrete surfaces, plasterboard, wood, plastic, plaster, with a previous application of Deco Primer Finish Isoplam®.
On metal, it is necessary to degrease the support and apply a coat of anti-rust additive Iso Ruggi Primer Isocolor® (evaluate the possibility of applying Plamfix79 Isoplam®).
When the primer has dried, apply colored Oxygreen Primer, previously diluted with 20% water, with a roller and allow it to dry completely.

PREPARATION OF THE PRODUCTS

Preparation of Oxygreen Powder + Liquid:

1 part powder by weight + 1 part liquid by weight.
The mixed product must be applied within 24 hours.

Preparation of Oxygreen Activator + Oxidant:

5 parts Oxygreen Activator (transparent) + 1 part oxidant Oxygreen Oxidant (light blue).
The product, once mixed, must be used within 6 hours for its correct operation.

APPLICATION

Mix Oxygreen Powder with Oxygreen Liquid in a 1:1 ratio until obtaining a smooth mixture with no lumps is obtained. The mixed product must be applied within 24 hours.
Apply a coat of mixture with a brush, roller or spatula unevenly.

When the support is almost completely dry, spray the mixture of Oxygreen Oxidant + Activator with Isoplam® Pump irregularly. Protective gloves and goggles are recommended.
Oxidant and Activator have to be used within 6 hours to prevent them from gradually losing their oxidation property.
Always check the spout of the sprayer for perfect nebulization. Spray preferably unevenly to diversify the effect.
Then protect with 2 coats of Oxygreen Protection.

It is recommended to consult Isoplam's Technical Department to identify the most suitable protective product. It should be noted that some final protective agents can tone down the colour, making it slightly darker.

It is recommended to test the product on a sample before using it and to use Isoplam® Professional Pumps.

Immediately clean the equipment with water after use.

It should be noted that blemishes, differences in shades and shadows are natural characteristics of the creation.

YIELD

On smooth surface:

With 1 Lt of Oxygreen Primer: approximately 10 sqm.

With 1 kg of Oxygreen Powder+ Liquid mixed together: approximately 4 sqm.

With 1 Lt of Oxygreen activator + oxidant mixed together: approximately 6 sqm.

With 1Lt of Oxygreen Protection you get a yield of about 10 square meters (one coat).

SAFETY AND PROTECTION

Oxygreen Powder + Liquid is water-based, so it is not flammable. Reaction to fire: M-0.

The mixture of Oxygreen Oxidant + Activator is irritant and corrosive. Use protective goggles, gloves, masks.

Oxygreen protection is a water-based product.

Do not apply at temperatures below + 5°C or above + 30°C.

Keep out of reach of children.

STORAGE

Store the products in a cool and dry place, away from UV rays in environments with temperatures between +5 ° C and + 35 ° C.

Storage time in unopened and sealed packages: 24 months for Oxygreen Powder, Liquid, Activator and Oxidant, the lot number indicates, in sequence, first 2 digits year/consecutive number of the day/last 2 digits month.

IMPORTANT:

The OXIDECOR® VERDERAME ISOPLAM® products are formulated to be used as in the application above. All information contained in this sheet is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use. The manufacturer declines all responsibility for the results of incorrect applications. It is advisable to always carry out tests on small surfaces before application. Data can be changed at any time. This sheet replaces and cancels previous ones.

OXIDECOR® VERDERAME ISOPLAM® products are intended for professional use. Isoplam Srl periodically organizes courses for its customers.